



15.0" XGA DiamondVue NEMA 4 (IP65) Panel Mount



This 15.0" DiamondVue flat panel display is designed to be placed in a variety of industrial and process control environments requiring a NEMA 4 panel mount that supports VGA to native XGA resolution. This display is auto sync compatible with most PC's video standards and satisfies a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ XGA Native Resolution
- ◆ Compact, Low Profile
- ◆ Wide Viewing Angles
- ◆ Optional Resistive or Capacitive Touch

Display Size
15.0 Inch

Panel Type
TFT Active

Native Resolution
XGA

Native Pixel Format
1024 x 768

Pixel Pitch
.297mm (w) x .297mm (h)

Active Display Area
11.973"(w) x 8.979"(h)
304.12mm(w) x 228.09mm (h)

Viewing Angle
LEFT/RIGHT: 80°/80°
UP/DOWN: 80°/80°

Contrast Ratio
500:1 Typical

Brightness
400 Nits Typical (1950 nits optional)

Back Light
50,000 Hours Typical

Colors Supported
16.7M

Input Connectors
HD15(F), Mini Din 4-way (S-Video),
Composite (BNC), DVI

Optional:
HD15(M) to 5xBNC(F) Interface
Cable

Video Input
Analog 0.7Vp-p / 75 ohm, Digital,
NTSC/PAL

Sync
TTL Separate H&V,
Combined, SOG

Power Source
90-264VAC Universal

Optional:
12VDC@ 2.25A

Power Consumption
27 Watts
4 Watts Sleep Mode

Temperature
Operating: 0 to 50°C
Storage: -20 to 60°C
Optional:
Operating: -20°C or -40°C

Humidity
Operating: 10 to 90% NC
Storage: 5 to 95% NC

Altitude
Operating: up to 10,000 ft
Storage: up to 40,000 ft

Dimensions
16.5"(w) x 13.65"(h)
419.1mm(w) x 346.45mm(h)

Cut Out Dimension
15.06"(w) x 12.2"(h)
382.52mm(w) x 309.88mm(h)

Depth Behind Panel
2.51"/63.75mm

Stud Size & Screw Length
10-32 x 1/2"

Weight
Unit: 10.5 lbs / 4.76 kg

Chassis Construction
16 gauge aluminum

Bezel Finish
Black Powder Coat on Aluminum
Optional:
NEMA 4X 316 Stainless Steel

Touchscreen
Optional:
Resistive or Capacitive

Touch Interface
USB

UNITRONIX Pty Ltd

PO Box 486, Morisset NSW 2264

NSW: Tel: 61 2 4977 3511 Fax: 61 2 4977 3522

WA: Tel: 61 8 9455 2424 Fax: 61 8 9455 2458

unitsyd@unitronix.com.au www.unitronix.com.au

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN
55024:1998, CISPR 22:2005,
CISPR 24:1997

Canada: ICES-003

Australia/New Zealand: AS/
NZS CISPR 22

CE

RoHS
WEEE



CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Capacitive Touch or Resistive Touch
- 1950 Nits Brightness
- HD15(M) to 5xBNC(F) Interface Cable
- 316 Stainless Steel NEMA 4X Front Panel
- 12VDC Power Supply
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming
- Chemically Strengthened Bonded Overlay on Non-Touch Screen