



15" NEMA 4X Fully Enclosed LCD



Compact

The VT150VS fully sealed NEMA 4X monitor is a rugged, industrial display designed to connect remote PCs to the production floor. With its moderate weight and very small footprint, the VT150VS series is ideal for applications where space is limited.

Rugged

The VT150VS monitor is fully enclosed in a sealed, 316 stainless steel, NEMA 4X chassis. The system has no external vents, so nothing can get under its skin, including weather, dust, dirt, moisture, oil, chemicals or other harsh contaminants. An internal heat management system keep it cool in environments where ambient temperatures approach 60°C -- without using outside air.

With its lightweight yet rugged construction, and either precabled or bulkhead connectors, the VT150VS is easily mounted on walls, stands, arms or other industrial equipment. With optional brackets, it conforms to VESA flat panel mounting standards.

FEATURES

- ◆ NEMA 4X sealed enclosure
- ◆ Water proof and dust proof
- ◆ Stainless steel construction
- ◆ Small footprint
- ◆ Flexible mounting options
- ◆ Resistive touch screen display (HMI)

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003
Australia/New Zealand: AS/NZS CISPR 22

CE
RoHS
WEEE



*Supports all VESA standard video formats

SPECIFICATIONS

Display

15" XGA TFT LCD

Resolution

1024 x 768

Viewing Angle

140° (H) / 120° (V)

Pixel Pitch

0.294mm

Display Colors

16.7M

Brightness

250 cd/m²

Contrast Ratio

600:1

Response Time

7 ms

Power Input

100-240 VAC 1.5A 50/60 Hz, IP67

Sealed Connector

Optional:

12/24V DC,

6 to 32V DC

Input Connectors

Standard: VGA

Optional: S-Video, Composite, DVI

Enclosure

316 Stainless Steel Sealed

Mounting

VESA - 100mm

Environmental

NEMA 4X

Water Proof

Dust Proof

IP66

Dimensions

16.15" (W) x 15.96" (H) x 3.9" (D)

Height is 12.09" when not allowing for the connections on bottom

Weight

15 lb

Temperature

Operational: -10° to 60°C

Storage: -40° to 65°C

Humidity

Operational: 0 to 90% RH NC

Storage: 0 to 95% RH NC

Touch Screen

Resistive, IP67 Sealed Connector

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

UNITRONIX Pty Ltd

PO Box 486, Morisset NSW 2264

NSW: Tel: 61 2 4977 3511 Fax: 61 2 4977 3522

WA: Tel: 61 8 9455 2424 Fax: 61 8 9455 2458

unitsyd@unitronix.com.au www.unitronix.com.au

OPTIONS

- High Brightness Sunlight Readable Model
- S-Video, Composite, DVI Video Input Connectors

www.vartechsystems.com