



20.1" UXGA NEMA 4 Panel Mount Display



This 20.1" flat panel display is a compact design to be placed in a variety of industrial and process control environments requiring resolutions from VGA to UXGA*. These displays are auto sync compatible with PC's video standards and satisfy a wide variety of industrial control and man-machine interface applications and are available in a variety of sizes.

SPECIFICATIONS

FEATURES

- ◆ Bright Active Matrix TFT Display
- ◆ HD15(F), DVI-D Pin, RCA, Mini Din
- ◆ Compact Low Profile
- ◆ Picture in Picture
- ◆ Anti-Reflective Protective Faceplate
- ◆ Optional Touch Systems

Marks of Conformity:

FCC47 CFR part 15, subpart B
EMC: EN 55022:2006, EN 55024:1998, CISPR 22:2005, CISPR 24:1997
Canada: ICES-003
Australia/New Zealand: AS/NZS CISPR 22
CE
RoHS
WEEE



*Supports all VESA standard video formats

Display Size

20.1 Inch

Panel Type

TFT Active

Resolution

VGA to UXGA*

Pixel Format

640 x 480, 800 x 600, 1024 x 768
1280 x 1024, 1600 x 1200*

Pixel Pitch

.255mm (w) x .255mm (h)

Viewing Angle

Left / Right: 88°/88°
Up / Down: 88°/88°

Active Display Area

16.172" (w) x 12.152" (h)
410.77mm x 308.66mm

Picture in Picture

Small Window: 3.6" (w) x 2.9" (h)
Med Window: 5.0" (w) x 4.9" (h)
Large Window: 6.5" (w) x 5.0" (h)

Contrast Ratio

800:1

Brightness

300 Nits Typical

Colors Supported

16.8M

Backlight

50,000 Hrs Typical

Video Input

0.7Vp-p / 75 ohm Digital

Sync

TTL Separate H&V,
Combined, SOG

Input Connectors

HD15(F), DVI-D Pin, (NTSC / PAL)
5 PIN MINI—DIN (S-Video)

Optional:

HD15(M) - 5xBNC(F) Interface Cable

Power Source

90-264VAC Universal

Optional:

24VDC @ 2.8A

Power Consumption

50 Watts @115VAC

8 Watts Sleep Mode

Temperature

Operating: 0 to 50°C

Storage: -20 to 60°C

Optional:

Operating: -20°C or -40°C

Humidity

Operating: 10 to 95%NC

Storage: 10 to 95 NC

Bezel Outside Dimension

20.466" (w) x 16.464" (h)

519.84mm(w) x 418.19mm(h)

Cut Out Dimension

19.130" (w) x 15.130" (h)

485.90mm(w) x 384.30mm(h)

Depth Behind Panel

3.310" / 84.07mm

Stud Size & Screw Length

10-32 x .62"

Chassis Construction

18 gauge Stainless Steel

Bezel Finish

NEMA 4

Black Powder Coat

Cold Rolled Steel

Optional:

NEMA 4X Stainless Steel

Touch Screen

Optional:

Resistive or Capacitive

Touch Interface

Serial

Optional:

USB

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

UNITRONIX Pty Ltd

PO Box 486, Morisset NSW 2264

NSW: Tel: 61 2 4977 3511 Fax: 61 2 4977 3522

WA: Tel: 61 8 9455 2424 Fax: 61 8 9455 2458

unitsyd@unitronix.com.au www.unitronix.com.au

OPTIONS

- Capacitive or Resistive Touch
- HD15 to 5BNC adapter cable
- Stainless Steel NEMA 4X Front Panel
- Optical Bonding for added Shock & Vibration protection and/or reduced solar reflectivity
- Integrated Heaters & Thermostat for extended Operational Temperature -20°C
- Transparent Thermal Heaters for -40°C Operational Temperature
- Private Label for OEM/VAR Applications
- ITO Glass for Heater or EMI
- Automatic Dimming Sensor
- Manual Full-Range Dimming