



32.0" VBOND WXGA Tabletop Mount Rugged LCD



VarTech Systems unique VBOND process seals either a top cover glass or touch screen directly to the face of the display bezel. This bonding process eliminates the air-gap between the display and the cover glass, vastly reducing reflective light, which causes visual washout of the display image. VBOND also enhances structural integrity by supporting the LCD assembly with the cover glass. The bond maintains perfect display uniformity while providing shock protection and elimination of fogging caused by trapped moisture accumulating in typical air gap assemblies.

SPECIFICATIONS

Display Size

32.0 Inch

Panel Type

TFT Active

Resolution Capabilities

1366X768

VGA to WXGA

Pixel Format

640x480, 800x600, 1024x768,
1280 x 1024, 1366x768*

Input Resolution

1360 x 768 @ 60HZ (Analog & Digital)

Frequency

Horizontal: 30K to 65KHz
Vertical: 56 ~ 75Hz

DDC

DDC 2B

OSD Control

RS232C, Push button,
IR Remote Controller

OSD Language

English, Japanese, Chinese

Viewing Angle

H:176° / V:176°

Contrast Ratio

1500:1 Typical

Brightness

500 Nits Typical

Colors Supported

16.7 M

Input Connectors

15 pin D-Sub, DVI, S-Video,
AV, Component

Communication Port

D-Sub 9 Pin, RJ145 In/Out
(Transport Protocol - RS-232,
RS-485 I/O)

Power Source

100-240 VAC (50/60Hz)

Power Consumption

165 Watts Normal Operation

15 Watts Standby Mode

15 Watts Power Off Mode

Temperature

Operating: 5° to 40°C (optional -20°C)

Storage: -20° to 60°C

Humidity

Operating: 85%RH

Storage: 85%RH

Response Time

6.5ms(GTG)

Multimedia

PIP, PAP, Zoom

Fanless Design

Yes

Source Auto Detect

Yes

Optional Touch Screen

Optical Imaging Touch Available

Dimensions

793mm x 483mm x 93.9mm

793mm x 511.7mm x 180mm (with stand)

Wall / Arm Mount Type

200mm X 200mm VESA

Weight (with stand)

16kg

Warranty

1 year (optional 2 year)

FEATURES

- ◆ Sunlight Readable VBOND enhanced LCD screen
- ◆ Bright Active Matrix TFT Display
- ◆ Rugged Metal Enclosure
- ◆ 1366 x 768 Max. Resolution
- ◆ Digital or Analog Interface
- ◆ Wide Viewing Angles
- ◆ 500 nits Brightness
- ◆ Multiple Video Input Selections
- ◆ Aspect Ratio: 16:9
- ◆ Optional Optical Imaging Touch Screen

CONTACT

HEADQUARTERS

11529 Sun Belt Ct.
Baton Rouge, Louisiana 70809

Phone 800.223.8050

International

001.225.298.0300

Fax 225.297.2440

E-mail

sales@vartechsystems.com

Website

www.vartechsystems.com

OPTIONS

- Protective Surface - 4mm (AG/AR), Tempered Glass
- Conformal coating to all internal system circuit boards
- -20°C Operational Temperature
- Optical Imaging Touch Screen

UNITRONIX Pty Ltd

PO Box 486, Morisset NSW 2264

NSW: Tel: 61 2 4977 3511 Fax: 61 2 4977 3522

WA: Tel: 61 8 9455 2424 Fax: 61 8 9455 2458

unitsyd@unitronix.com.au www.unitronix.com.au

www.vartechsystems.com