

RPC-910 4U Rackmount Flat-Door Massive Storage Industrial Chassis



Features

- 4U 19" Rackmount Flat-Door Massive Storage Industrial Chassis
- 8x 3.5" Disk Drive Bay, 2x 5.25" Front Accessible Disk Drive Bay
- Front 2x USB Port
- Four cooling fans designed for optimizing the system's airflow
- Lockable Front Door for Protecting the Running System
- Front LED indicator for PWR and HDD
- Special hold-down clamp with flexible adjust

Specifications

System	
Construction	The enclosure is heavy-duty Steel, The panel is aluminium
Technics	Surface machining of spray-paint, high temperature firing
Storage	Internal: 8x 3.5" Disk Drive Bay External: 2x 5.25" Disk Drive Bay
System Fan	Two front cooling FANs, Two top cooling FANs
Front Panel	1x Reset Button 1x Power Switch 1x HDD LED 1x Power LED 2x USB Port
Rear Panel	AT/ATX back window
Backplane support	Industrial Backplane or normal ATX PC board
Air filter	One hole for air filter on front panel
Color	Black/Beige
Power	AT/ATX
Dimensions	19"×21.26"×15.35", 482mm×540mm×177mm(W×D×H)
Carton Size	26.97"×21.5"×11.42", 685mm×546mm×290mm(W×D×H)
Net Weight	29.4lb±1lb (13.34Kg±0.5Kg)
Gross Weight	34.66lb±1lb (15.72Kg±0.5Kg)
Environmental	
Operating Temperature	32 131 (0 55)
Storage Temperature	-4 185 (-20 80)
Operating Humidity	5 95%
Storage Humidity	5 95%@40 , non-condensing
Vibration	0.5G/5 500Hz/operation (3.5" Hard Disk Drive) 1.5G/5 500Hz/no operation
Shock	15G peak acceleration (11 m sec. duration), operation 30G peak acceleration (11 m sec. duration), non operation
EMC	FCC/CE Class B

Packing List

- **0811500029** Power Cord
- **4000060089** HDD Screw
- **1630350609** PSU Screw
- **0000000000** USB Cable
- **9041019509** Removable Cotton filter
- **0000000000** rubber column

Ordering Information

- **RPC-910**
4U 19" Rackmount Chassis, Shell/Black, lockable door, 2x USB, PC board/industry backplane supported, 7x 3.5" drive bay, 3x 5.25" drive bay, 2x intake fans, 2x exhausted fans certification: FCC&CE Class B

Power Supply Options

- **PW-300**
300W ATX PSU, input: 180~260V/AC@47~63Hz, output: +3.3v, +5V, +12V, -12V, +5VSB
- **PW-350**
350W ATX PSU, input: 180~260V/AC@47~63Hz, output: +3.3v, +5V, +12V, -12V, +5VSB

Backplane Options

- **PBP-08P4**
8-slot Backplane, 2x PICMG1.0 slots, 4x PCI slots, 2x ISA, Size: 270mm×191mm, AT/ATX supported
- **PBP-14I**
14-slot Backplane, 14x ISA, Size: 315.5mm×173.5mm, AT/ATX supported
- **PBP-14P4**
14-slot Backplane, 2x PICMG1.0 slots, 4x PCI Slots, 8x ISA, Size: 323mm×270mm, AT/ATX supported

Rear I/O shielding Options

- **PRC-910-AT**
AT I/O shielding, can be applied to industry backplane
- **PRC-910-ATX**
ATX I/O shielding, can be applied to PC board

